

eagle *edge*

3D CBCT | PAN | CEPH



A COMPREHENSIVE
SOLUTION WITH
A MULTITUDE OF
POSSIBILITIES

DABI ATLANTE

EAGLE EDGE 3D

3-in-1



4 Possible configurations:

- | | |
|-------------------|-------------------|
| SFOV | MFOV |
| PAN + CBCT | PAN + CBCT |
| PAN + CBCT + CEPH | PAN + CBCT + CEPH |



With exclusive technology from Dabi Atlante and innovative algorithms, the *Dental CT Scanner AXR* is prepared for high-flow demands and provides a complete solution in a single product. It is intelligent, precise, highly accurate in diagnosis, and has a performance that will impress the most demanding professionals.

Upgrade options:

(at a future date of your choice)

- Equipment:**
- | | |
|--|---|
| PAN + CBCT | PAN + CBCT with CEPH |
| SFOV CBCT sensor
(FOV up to 14x9cm) | MFOV CBCT sensor
(FOV up to 16x21cm) |

THE IDEAL FOV FOR EACH NEED



Patient Motion Correction (PMC)

The Eagle Edge algorithm automatically corrects the image, ensuring high exam quality, avoiding repetitions and offering greater accuracy for making diagnoses.




Without correction




With correction

Without the reduction of artefacts



With the reduction of artefacts




Metal artefact reduction - MAR

The Eagle Edge line features three processing levels that can be chosen to correct gutta-percha deformities, implants and/or full arch prosthesis and metal restorations, in addition to automatic metal reduction.

UHD mode for endodontics

Eagle Edge has different resolutions with Isotropic Voxel:

- 48 μ m to 200 μ m for the Eagle Edge 0.2FS
- 75 μ m to 400 μ m for the Eagle Edge



3D CLINICAL IMAGES

FOV 5x5

5x5 - ENDO


This small FOV is optimal for local diagnostics such as single implant planning, 3rd molar extraction and endodontic procedures. It has a resolution of 48 μ m and has 4 distinct programs, to better adjust the patient's exposure dose according to the purpose of the exam.



FOV 9x6

9x6 - MAXILLA OR MANDIBLE


Allows the visualization of 1 arch (maxillary or mandible) and TMJ (left or right condyle separately).



FOV 9x9

9x9 - COMPLETE MANDIBLE

For the visualization of the entire arch, including the mandible, maxilla and mandibular ramus.



FOV 14x9

14x9 - ORAL AND MAXILLOFACIAL

View the mandible, maxilla, airways, sinuses and TMJ (closed and/or open) in a single volume.



FOV 16x9

16x9 - EXTENDED MANDIBLE

Allows visualization of the mandible, maxilla, airways, sinuses and TMJ (closed and/or open) in a single volume.



FOV 16x15

16x15 - CRANIUM

Ideal for orthodontics and orthognathic surgery - for a diagnosis of the entire maxillofacial region.



FOV 16x21

16x21 - COMPLETE CRANIUM

Ideal for orthodontics - providing an image of the entire maxillofacial region.



EAGLE EDGE 2D

Pan + Ceph



3 Possible configurations:

- PAN
- PAN + CEPH (1 sensor)
- PAN + CEPH (2 sensors)



The Eagle Edge 2D's features make it stand out in its usability and image quality. Its optimized filters adapt the images according to your needs and its multislice feature enables you to navigate between 41 panoramic slices - so you can view the exact structures you need to. In addition, the reconstruction algorithms guarantee extraordinary focus and contrast in each acquisition.

Upgrade options:


(at a future date of your choice)

Equipment:

- PAN PAN with CEPH
- PAN PAN + CBCT SFOV / MFOV
- PAN PAN + CBCT SFOV / MFOV with CEPH

Filters

Eagle Edge machines feature optimization filters, including brightness, contrast, and layer thickness adjustments, empowering you to adapt your images to your preferred style. This flexibility ensures that you can deliver the highest-quality images to meet the demands of your target market.




Multi-slice Panoramic

The Multi-slice panoramic captures multiple layers of panoramic images. It is an innovative tool that allows the observation of the desired structures, adding depth to the panoramic examination.



Mobility
Cutting plane



Multilayer
41 layers

Your Upgrade Journey

1

Install
2D Pan



2

Add
Ceph Arm



Upgrade time
Installation - 20min
Calibration - 1h

3

Upgrade 2D
sensor to 3D
SFOV CBCT sensor



Upgrade time
Installation - 60min
Calibration - 3h30min
(Excl. Ceph: 3h)

4

Upgrade SFOV
sensor to
MFOV sensor



Upgrade time
Installation - 30min
Calibration - 3h30min
(Excl. Ceph: 3h)

Cost effective ▪ Limited downtime ▪ No noise or dirt disruptions ▪ No time limit to opt-in for upgrades.

PANORAMIC CLINICAL IMAGES

Fast Pan



Bitewing



Maxillary Sinuses



Panoramic



Children's Panoramic



Enhanced Ortho



TMJ



CEPHALOMETRICAL CLINICAL IMAGES

Lateral Ceph



Fast Ceph



AP/PA Frontal Ceph



Oblique Ceph



Carpal Ceph



3D ALGORITHMS

OPTIMIZING YOUR WORK-FLOW AND DIAGNOSTIC ACCURACY



Patient Motion Correction (PMC)

During exams, patients commonly make micro-movements, affecting the final exam result.

The Eagle Edge algorithm automatically corrects the image, ensuring high exam quality, avoiding repetitions and offering greater accuracy for making diagnoses.



Without correction




With correction


Metal Artefact Reduction (MAR)

The Eagle Edge line features three processing levels that can be chosen to correct gutta-percha deformities, implants and/or full arch prosthesis and metal restorations, in addition to automatic metal reduction.


This tool also allows image reprocessing, for a better diagnosis, preventing the need to generate new exposure to the patient.




Without MAR



With MAR



Without MAR



With MAR

2D ALGORITHMS


INTELLIGENCE APPLIED TO PANORAMIC EXAMS, GENERATING STUNNING IMAGES.

Eagle Smart Contrast

An innovative algorithm, working in all parts of the image, to treat and improve the contrast of each area individually. The result is a homogeneous and noise-free image, allowing the clear visualization of details, and therefore, better diagnosis.

Eagle Eye

Eagle Eye software features an innovative function that delivers a final image with greater detail and definition, especially in the region of incisors and canines, TMJ and root canals.




The combination of algorithms allows the reconstruction of an optimized panoramic image. Eagle Eye technology brings the exceptional diagnostic quality to the most challenging cases.

VERSATILITY AND INNOVATION: THE EAGLE EDGE FOCUS

V-Beam

The Variable Cone Beam developed for Eagle, guarantees high definition in images with FOVs of 5x5, 9x6, 9x9 and 14x9 (SFOV sensor), and allows the capture of larger images, adding the options of FOVs of 16x9, 16x15 and 16x21 (with the MFOV sensor). Eagle Edge is the complete solution for 3D diagnostics, especially in endodontic, implantology and orthodontic applications.





A product with different tube voltages

The *Dental CT Scanner AXR* comes with a 120kV tube on its 3D SFOV and MFOV machines. Operation at 120 kV, combined with special radiation filters, produce beams with higher average energy, reducing photons of lower energy, which provides two benefits:

1 - Fewer artefacts in the image, due to the reduction of Beam Hardening in the patient.

2 - Reduction in the production of low-energy beams, which can be filtered using a more efficient set of filters - resulting in a lower radiation dose and a better image quality.



Stitching

Moving the chin rest enables large FOV tomographic images (16x15 and 16x21) to be performed in continuous operation. This avoids patient repositioning, which minimizes position deviations between individual captures.


By capturing in a single sequence and utilizing automatic stitching (automatic volume merging) along with PMC (Patient Motion Correction), we produce high-quality images, minimizing artefacts and decreasing the time required for image capture and processing.

- Automatic positioning
- 3 cm overlap between the layers
- Motion correction ensures the uniformity of images
- Reducing the odds of rework



3 Axes

The advanced movement system includes three axes (two orthogonal directions and one rotation), which allows greater flexibility in the preparation of radiographic profiles, optimization of the thickness of the cutting plane and constant vertical recovery.



Program



Choose the ideal programme for your needs

Choose the ideal resolution for each exam, adjusting exposure time and voxel size according to the exam objective. Control the exposure to get a higher resolution or an image with a lower exposition.

LD

STD

HD

UHD

MANAGEMENT SYSTEM

EAGLE EYE SOFTWARE


Eagle Eye is a software focussed on user-friendliness, that examines performance gains in reporting. It assists professionals in accomplishing what they need to in as few clicks as possible - facilitating patient flow.

Dental Imaging Software - Eagle Eye: Anvisa 10101130091




REGISTER

Simple and intuitive: register users (with different levels of permission), dentists and patients.



SEARCH

Focused on user-friendliness: search for users, dentists and patients.



CAPTURE AND EDIT

Capture 2D and 3D images, and edit 2D images, all in the same software.




EXPORT

Export images and DICOM files in formats compatible with most software systems worldwide.



PANORAMIC REPORTS

Speed and practicality: Perform panoramic reports directly in the acquisition software.




Eagle Eye Connection

The Dicom Worklist tools, communication via PACS, and acquisition via TWAIN driver, enable immediate sending of images generated by the equipment, to all of the leading image management and sharing programmes.

Eagle Eye IP (Implant Planning)

Implant Planning is a tool that allows you to simulate implants directly on your computer.

You can simulate the position of implants in two-dimensional imagery, identify the mandibular canal and take measurements.




Eagle Eye Ceph (Manual)

A software tool for manual cephalometrical trace reports.

(Available protocols: MCNAMARA, USP, Ricketts, Steiner, Rocabado, Tweed, among others.)

Eagle Eye Ceph AI Diagnostic *

Applying scientifically recognized protocols, Artificial Intelligence accelerates productivity in complex analyses and adds efficiency to your business.



* Optional

ONDEMAND SOFTWARE LINE

OnDemand3D DENTAL

Optionally, the Eagle Edge line can be accompanied by OnDemand3D Dental software, the leading software in the world due to its user-friendly interface, resource availability, processing speed and security.

Viewer creation

With the OnDemand3D software you can create viewer access. This enables you to share exams with your clients and patients who do not have a specific programme for viewing DICOM files.

This viewer will have access to all the diagnostic tools of the licensed version, such as positioning implants, taking measurements and panoramic cuts.


Report

OnDemand3D makes reporting easier and simpler for professionals by offering multiple templates for every use.

Create your own report template with the X-Report Template Designer. These reports can be stored both in the database and on the computer, in HTML, PPT or PDF format.

CONVERT TO STL

Convert DICOM data to STL data using OnDemand3D for use in CAD/CAM software and 3D printers.



PRODUCT SPECIFICATION

COMPARISON TABLE

		EAGLE EDGE 3D MFOV	EAGLE EDGE 3D SFOV	EAGLE EDGE 2D
PRODUCT	MODEL	AXR120	AXR120	AXR90
	FOCAL POINT (mm)	0.5	0.5	0.5
	VOXEL (µm)	75 - 400	75 - 400	NA
	FOV (FIELD OF VIEW)	5x5, 9x6, 9x9, 16x9, 16x15 & 16x21	5x5, 9x6, 9x9, 14x9	NA
	CEPH	O	O	O (1 OR 2 SENSORS)
	TUBE VOLTAGE (kV)	60 - 120	60 - 120	60 - 90
	TUBE CURRENT (mA)	3 - 16	3 - 16	3 - 16
	POWER SUPPLY VOLTAGE (V)	110/127/220/240 AC	110/127/220/240 AC	110/127/220/240 AC
	MINIMUM EXPOSURE TIME	10s	10s	10s
	BITE BLOCKS	5 BITE BLOCKS & 3 CHIN RESTS	5 BITE BLOCKS & 3 CHIN RESTS	5 BITE BLOCKS & 3 CHIN RESTS
	RESOLUTION	4.2 lp/mm	4.2 lp/mm	5 lp/mm
	GRAYSCALE	16 BIT	16 BIT	16 BIT
	ROTATION	360°	360°	350°
	Supported protocols	DICOM 3.0, TWAIN, VDDS		
DICOM Modules	THE- compliant (Print; Storage Commitment; Query/Retrieve)			
IMAGE PROGRAMMES	SOFTWARE - LICENSES	EAGLE EYE (1 SERVER + 5 CLIENTS)	EAGLE EYE (1 SERVER + 5 CLIENTS)	EAGLE EYE (1 SERVER + 5 CLIENTS)
	ADULT PAN	S	S	S
	INFANT PAN	S	S	S
	FAST PAN	S	S	S
	SINUSES	S	S	S
	TMJ	S	S	S
	BITE WING	S	S	S
	IMPROVED ORTHO	S	S	S
	MULTI-SLICE	S	S	S
	2D FILTERS - ACQUISITION MODE (ORIGINAL, 1, 2, 3) AND OPTIMIZED AUTO PAN	S	S	S
DOSE / RESOLUTION	LD/STD/HD/UHD	LD/STD/HD/UHD	NA	
SOFTWARE: EAGLE EYE	PATIENT AND EXAMINATION MANAGEMENT	S	S	S
	TWAIN	S	S	S
	IMAGE MANAGEMENT	S	S	S
	POST IMAGE PROCESSING	S	S	S
	EXPORT TO EMAIL	S	S	S
	DICOM (IMPORT, SAVE, SEND)	S	S	S
	MEASUREMENTS AND NOTES	S	S	S
	PRINT TEMPLATE	S	S	S
	EAGLE CONNECTION (GENERATION OF VIEWS, PACS COMMU- NICATION, DICOM WORKLIST)	S	S	S
	EAGLE CEPH (CEPHALOMETRIC TRACE)	S	S	S
	EAGLE EYE IP (IMPLANT PLANNING)	S	S	S
	CEPHALOMETRY - IMAGE SIZE	S	S	S
CEPHALOMETRY - ARTIFICIAL INTELLIGENCE	O	O	O	
SOFTWARE: EAGLE TOMOGRAPHY	MAR - ARTEFACT CORRECTION			NA
	PMC - PATIENT MOTION CORRECTION	S	S	NA
	3D RECONSTRUCTION - CERA	S	NA	NA
	3D VIEWER	S	S	NA
	ON DEMAND	S	S	NA
UPGRADES	CEPH	S	S	S
	3D - SFOV			S
	3D - MFOV		S	S

COMPUTER CONFIGURATION


MINIMUM REQUIREMENTS

For optimal performance, we recommend that the computer connecting to Eagle products, meet the minimum recommendations presented in the table below.

Product	2D	3D
Operating system	Windows 10 Professional - 64 BIT	Windows 10 Professional - 64 BIT
CPU	Intel Core i5 Gen 10 Cache 12 MB 4.0 GHz or superior	Intel Core i7 Gen 10 Cache 12 MB 4.0 GHz or superior
HDD	1 TB	1 TB
RAM	8 GB (DDR4)	16 GB (DDR4)
USB 2.0	1 USB Port	2 USB Ports
PCI Express	PCI Express (PCIe)	PCI Express (PCIe)
Dedicated network card	Gigabit Ethernet (1000Mb/s), JumboPacket 9KB (Intel i350-T1, Intel Gigabit CT, PCE-1G-01-LP)	Gigabit Ethernet (1000Mb/s), JumboPacket 9KB (Intel i350-T1, Intel Gigabit CT, PCE-1G-01-LP)
Power supply	400W or superior*	500W or superior*
Monitor	Resolution 1920x1080	Resolution 1920x1080
Video card		NVidia Geforce RTX 4060 8GB or superior. Recommended for faster rebuilds: NVidia GeForce RTX 4070 12GB or superior


*Compatible with PCI Express and NVidia card connectors.

DIMENSIONS




RECOMMENDED ROOM SIZE

Imperial dimensions



Metric dimensions



* Minimum room lengths are only viable for rooms with a sliding, or outward opening door.

Local guidelines may vary. Seek guidance from your local health authorities for further information and requirements regarding the installation and operation of the equipment.



www.dabiatlante.com

Eagle Edge is an Alliage brand of *Dental CT Scanner AXR*, as registered by Anvisa 10101130088. Dental Imaging Software - Eagle Eye: Anvisa 10101130091. The assembly of the equipment must be paid for by the buyer (client) and carried out by an accredited technician. The package must remain closed until the technician arrives, if it is violated, the product warranty will be cancelled.

Illustrative photos. Colours may have changed in graphic reproduction. Dabi Atlante reserves the right to make changes to the design and technical specifications upon authorization by ANVISA to continue improving them. 51000000110 - Revision: July/2024.